



CM2200FDW

Features

Specs

Where to buy

| | |
|----------------------------|--|
| Model | CM2200FDW |
| Printing | |
| Print speed | 24ppm (A4) / 26 ppm (Letter) (Black & Color) |
| First print out time | Less than 10.6s |
| Recommended monthly volume | 50000 pages |
| Resolution(dpi) | 600 x 600dpi(Optical) 4800 x 600dpi(Enhanced) |
| Printer language | PCLm/PS3/PCL6/PCL5 |
| Duplex Mode | Auto |
| Paper handling | |
| Paper input | 250 pages |
| Paper output | 100 pages |
| Media type | Plain Paper/Colored Paper/Card Stock/Labels/Letterhead/Preprinted/Bond/Glossy/Light Paper/Heavy Paper/Rough&Cotton/Recycled/Envelope |
| Media size | A4/A5/A5LEF/A6/JIS B5/Oficio/Hagaki Postcard/Statement/Executive/Letter/Folio/Legal/General paper DL envelope/C5 envelope/ B5 envelope/7*3/4 envelope/ #9 envelope/#10 envelope |
| Media weight | Standard tray: 60-120g/m ² Multipurpose tray: 60-176g/m ² Duplex: 60-105g/m ² ADF: 60-90g/m ² |
| Scan to | USB, Email, FTP, PC |
| General | |
| Dimensions (W×D×H) | 411.2*394.1*344.4mm |
| Weight (with cartridge) | 19.4kg |
| Recommended environment | Temperature range: 10-32°C (50°F-90°F) Humidity range: 20% - 80% |
| Power | 220-240v; 50/60Hz; 2.6A |
| Noise | Print(black/color): 50/51dB(A) Duplex print(black/color): 49/51dB(A) Sleep/Hibernate/Ready/Idle: 14dB(A) Mute mode printing: (single,black color):46/46dB(A) Mute mode printing: (duplex,black color):45/45dB(A) |



| | |
|--|---|
| Power consumption | Print: 395W Duplex print: 275W Ready: 17W Sleep: 0.9W Hibernate: 0.1W |
| Operating system compatibility | Windows Vista/Win7/Win8/Win8.1/Win10/ Server 2008/Server2008 R2/Server 2012 R2/Server 2016 |
| | Airprint for the print Aircan for the scan |
| | Ubuntu 18.04/16.04 |
| Connectivity | Hi-Speed USB 2.0 10/100/1000 BaseTX Ethernet(RJ-45) 802.11b/g/n Wireless |
| Processor speed | Dual Core,1GHz |
| Memory | 512MB |
| Consumable * | |
| Toner cartridge | CTL-2000 Series |
| Starter cartridge capacity(K/CMY) | 750pages/500pages |
| Standard cartridge capacity(K/CMY)(K/CMY) | CTL-2000C/2000M/2000Y/2000K: 1.5K/1.5K CTL-2000HC/2000HM/2000HY/2000HK: 3.5K/3.5K |
| Waste toner bottle capacity | CWT-2000: 15K |
| * Average continuous black or continuous composite CMY declared cartridge yield up to this number of standard pages in accordance with ISO/IEC 19798. Actual yield may vary based on other factors such as paper size and feed direction, toner coverage, percentage of black-only printing, and average print job complexity. | |
| The model is only available in some countries. | |





PRINTING SHOULD BE
SIMPLE

Cartridges | Single Function Printers | Color Printers | Multifunction Printers



Need Help?

Contact us now ▼

Skype 
Service Center 

[Drivers & Downloads](#) [Manual and FAQ](#) [Service Hotline](#)



Get the latest deals

Stay connected with latest updates and newsletters

[About Pantum](#)
[Company Profile](#)
[Contact Us](#)
[Pantum News](#)
[Work at Pantum](#)

[Partners](#)
[Pantum Activities](#)
[Partner Center](#)

Social Media



[Warranty Terms & Conditions](#)
[Drivers & Downloads](#)
[Customer Service Hotline](#)
[Service Center](#)
[Android APP Download](#)



This site uses cookies for various purposes including enhancing your experience, analytics, and ads. By continuing to browse this site or by clicking "Accept and close", you agree to our use of cookies. [For more information, read our Cookies page.](#)

Accept and close

